1 **Product Name:** SMA coax cable assembly – SMA connector to 2 pin Socket (0.1" - 2.54mm pitch) RG174 coax cable assembly 12" (30cm) **Product Description:** RG174 Coax cable assembly with Standard SMA connector to 2 pin socket connector. Maximum attenuation of -1.4dB, with 30pF capacitance. Length of RG174 coax cable: 12" (30cm) 20u" Gold plated socket pins mating with any standard 0.025" (0.64mm) square or round header Socket Pitch: 0.1" (2.54mm) SMA: 35u" gold plated SMA (core) ZX00011112, ZX00021112 are member of ZX00SMAS-x SMA to 2 pin socket cable assembly which is offered in five different lengths: 4.72", 8", 12", 24" and 36". An approved cable assembly for Keysight (Agilent) ≤ 2GHz Infinium S-Series oscilloscope, and N7020A Power Rail Probe and other **2 Pin Socket :** The 2 pin socket is marked + -, indicating GND and Core wire network analyzers and test equipment The "-" contact is connected to the SMA case, Ground. The "+" contact is connected to the SMA signal pin, the core. Application: Complementing Keysight (Agilent) Tektronix and Lecroy scope, test equipment ZX00011112, ZX0021112 are an approved Keysight (Agilent) cable assembly ZX20x series breakout adapters, or any general testing needs. Converting SMA connector to 2 pin socket using RG174 coax cable for ≤ 2GHz Infiniium S-Series oscilloscope, and N7020A Power Rail Probe. network analyzers and test equipment Mates with: Header posts with 0.025" (0.64mm) SQ pin header with post length 0.23" (5.83) Header pitch: 0.1" (2.54mm) SMA connector mates with standard SMA connector, please see ordering information. **Coax Cable information:** RG174 Type: -1.4dB (max.) Attenuation: Current Rating: 5A Capacitance: 30pF Length: 12" (30cm) Flammability: UL 94 V-0 Flame resistance: compliance with IEC 60332-3-24 Socket: Plating: 20u" gold plated 0.1" (2.54mm) pitch Pitch: 0.025" (0.64mm) Square header post Mates: Insulator Material: Black LCP Contact Material: Phosphor Bronze Approval: ZX00011112. ZX00021112 are an approved cable assembly for the following Keysight (Agilent) products: **Ordering INFO:** 1- Approved Keysight (Agilent) cable assembly for ≤ 2GHz Infiniium S-Series oscilloscope. Part Number SMA connector type 2- Approved Keysight (Agilent) cable assembly for use with N7020A Power Rail Probe. SMA Jack (Standard) ZX00011112 ZX00021112 SMA Plug В ALL ZEBAX products are RoHS compliant and Lead Free unless otherwise indicated. ZEBAX TECHNOLOGIES SANTA CRUZ, CA U.S.A (831) 222-0717 WWW.ZEBAX.COM ASSEMBLY DRAWING SPECIFIED DIMENSIONS ARE INCHES (MM). ITEM: ZX00011112 ZX00021112 ROHS COMPLIANT SMA coax cable assembly - SMA to 2 pin DESCRIPTION: ALL ZEBAX TECHNOLOGIES DESIGN SPECIFICATIONS, DRAWINGS, PUBLICATIONS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." ZEBAX MAKES NO WARRANTIES, EXPRESSED, socket coax RG174 cable assembly 12" IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NO INFRINGEMENT. MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, Information furnished is believed to be accurate and reliable. However, Zebax Technologies assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use. CHECKED: DRAWN: REVISSION: 1.0 Specifications mentioned in this publication are subject to change without notice. This publication replaces all other information previously supplied. Zebax Technologies products are not authorized as in life support devices or systems

M. MARINA

MATTHEW

SHEET: 1 OF 1