

Product Name: ZX202HD EDID EEPROM with HOTPLUG & CEC test points

Product Description: Extended Display Identification Data, EDID, module supporting EDID standard published by VESA. Full access to Consumer Electronics Control, CEC, as well as HOTPLUG Detection, HPD, signaling for full test coverage of electrical and protocol standard. **ZX202HD** holds 5 different EDID EEPROMs at any time. Each EEPROM is enabled by placing the SHUNT on J9. Only one EEPROM may be selected at any time. Each EDID EEPROM is tailored for different resolution and frame per seconds, fps. ZX202HD is offered with onboard EDID EEPROMs supporting the following resolutions and fps. User may replace any of the EDID EEPROM as required:
4K 60Hz 4K 30Hz 1080p 120Hz 1080p 60Hz

Additional EDID configuration may be used for required resolution / protocol using Zebax Programmer, ZX202PR, or any general purpose EEPROM programmer.

Full HOTPLUG, HPD, test coverage using onboard resistive load or external sources (**function generator**), emulating real time HPD droop and ripples. Ensure source HPD circuit design without compromise.

ZX202HD provides full access to CEC signaling, enabling internal or external test coverage for monitoring as well as inducing pre-defined protocol & test methodology mechanism.

Application: High Definition Multimedia Interface, HDMI, Display Port, DP Electrical HotPlug, CEC, VESA compliance

Operating frequency: DC to 1GHz signal bandwidth at the header landing pad

Mates with : **SMA connector** mates with standard SMA cable assembly, please see ordering information
Wire assembly mating with ZX200x or any other 0.025" (0.63mm) SQ pin socket mating with post header at length 0.23" (5.83mm)

Test procedure:

EDID - EDID selection is accomplished by enabling DDC-SDA (SDA) to the selected EEPROM (selected by placing SHUNT on J9 pins). Table below lists the EDID EEPROM labeling for the pre-programmed resolution & frame per second, fps. To Select, place the SHUNT on J9. **U2-4K60fps** in order to select 4K at 60Hz display resolution. Custom design EDID may be inserted into any of the U1 .. U6 sockets. No need to remove any of the EEPROM from its socket, the SDA signal routing is controlled by the SHUNT placed on J9.


Mfr. ID	ZBX			
Product Code ID	0202			
Labels	64	63	16	76
Mode	4K 60Hz	4K 30Hz	1080p 60Hz	720p 60Hz
CLK (MHz)	594	297	148	74.25
Resolution	3840x2160	3840x2160	1920x1080	1280x720
Product Name	HDMI TPA 594	HDMI TPA 297M	HDMI TPA 148M	HDMI TPA 74M

HOTPLUG –


- 1- Connect J7 to HPD of HDMI test board (ZX200x)
- 2- Select HPD supply voltage, Default: J8 – Place shunt on 5V – HPD_VS.
- 3- Select resistive load, default 1.2KΩ – R6
- 3- Press and Hold **S1** for minimum of 1 seconds
- 4- Sink device should detect the HPD transition and initiate DDC acquisition.

Please note- user may apply External Power Supply at HPD_VS in order to test source HPD circuit detection.

CEC – 1- J3, J4, J5 Provide CEC routing configuration for monitoring as well as applying external CEC signaling.




Circuit Diagram



Note:

- 1- Shunt default settings:
 J8: 5V – HPD_VS
 J6: R6 1.2KΩ
 J3: 1-2
- 2- All onboard resistors and capacitors are 0402 SMD package
- 3- All Headers are 0.1" (2.54mm) pitch, through hole headers.
- 4- For purpose of simplification of the circuit diagram, all supply voltage decoupling capacitors, and line filters (DDC) are omitted.
 All EEPROMs have 0.1uF decoupling capacitors.
 HPD_VS (J8.2) has 0.1uF to GND
 DDC_SDA, DDC_SCL (SDA, SCL) signals have line filter as below.




Ordering INFO:
 Part Number
 ZX202HD

Package includes:

Item	Part number	Quantity	Description
1	ZX202HD	1	EDID EEPROM with HOTPLUG & CEC test points
2	ZXJS1173-05	1	Wire assembly – HDMI to ZX202HD interface cable assembly
3	ZXJS1173-HD	1	Wire assembly for HDMI EDID interface cable assembly, Note 1
4	ZX00020212	1	SMA Plug to SMA Plug cable assembly 12" long, Note 2
5	ZX00WT-09NM	0	SMA Wrench Torque 5/16" (8mm)
6	ZX202PR	0	EEPROM Programmer

Notes: 1- Supplied wire assembly enables to interface with 3rd party modules.
 2 - Interfacing with HOTPLUG signal from test board.



Note
 ALL ZEBAX products are RoHS compliant and Lead Free unless otherwise indicated.

ZEBAX TECHNOLOGIES
 SANTA CRUZ, CA U.S.A (831) 222-0717
 WWW.ZEBAX.COM

SPECIFIED DIMENSIONS ARE INCHES (MM). ROHS COMPLIANT	ASSEMBLY DRAWING
	ITEM: ZX202HD
DESCRIPTION: ZX202HD EDID EEPROM HOTPLUG with full CEC signaling access	
CHECKED: M. MARINA	DRAWN: SLAVIK
	REVISION: 1.0
	SHEET: 1 OF 1

Notice
 ALL ZEBAX TECHNOLOGIES DESIGN SPECIFICATIONS, DRAWINGS, PUBLICATIONS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." ZEBAX MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NO INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE.
 Information furnished is believed to be accurate and reliable. However, Zebax Technologies assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use. Specifications mentioned in this publication are subject to change without notice. This publication replaces all other information previously supplied. Zebax Technologies products are not authorized as in life support devices or systems.