

Volume 3, Issue 8

NEWS LETTER

High quality SMA SMP IPEX and flying wire cable assembly

Cable assembly

Zebax offers variety of high quality SMA SMP IPEX and flying wire cable assemblies for high speed applications.

ZX00SMAS ZX00SMAS

 50Ω SMA connector to 2 pin **Socket** or 2 pin **Header**. Ideal cable assembly for **≤2GHz** applications. Maximum 0.53dB attenuation. **Application:** Signal and power measurements

ZX00SMAH



ZX00SMA-IPEXMHF4L ZX00SMA-IPEX37 ZX00SMA-IPEXMHF4L ZX00SMA-IPEX37 are SMA cable

Application: Pre-Bringup, bringup, test, debug

measurements, antenna, HSIC interface and more.

assembly converting 50Ω SMA connector to IPEX37 and IPEX MHF4L connectors. Ideal cable assembly for signal

ZX00SMA-SMP



ZX00SMA-SMA

1- SMA Jack to SMA Jack 2- SMA Plug to SMA Plug

Ohms SMA connectors.

ZX00ACC-SS flying wire

Offers High frequency 50Ohms RF High Speed util RG405 coax cable assembly. The cables are offered in Jack or Plug configuration. The ZX00SMA-SMP cassemblies are rated at <1.2dB insertion loss at 20GHz.

ZX00SMA-SMA is SMA cable assembly offered in 36"

The cable assembly utilizes RG316U coax cable with 50

Application: Pre-Bringup, bringup, test, debug

Application: Pre-Bringup, bringup, test, debug

Application: Pre-Bringup, bringup, test, debug

length with the following configurations:



28guage, AWG, flying wires with pin socket at each end. The $\underline{\sf ZX00ACC\text{-}SS}$ are offered in 3", 6", 9" and 12"

You're receiving this email as you have subscribed to the Zebax.com newsletter or refereed by colleague. You may reply to this email with "unsubscribe" at subject line if no longer wish to receive email communications from Zebax at any time. Questions or comments ? email us at contact@zebax.com





